

A worker in a white protective suit and mask is spraying a wooden frame in a factory. The worker is wearing a white long-sleeved shirt, white pants, and a black and red protective mask. They are holding a spray gun connected to a hose. The background shows a factory setting with wooden frames hanging from a chain.

Registratie natte laagdikte

Concept II & III

Tweelaags systeem

Wijzonol

vakverf sinds 1916

Registratie natte laagdikte



Weeknummer:

Ordernummer:

Project:

1 laag WIJZONOL ECO PRIMER A + 1 laag WIJZONOL ECO TOPCOAT A GLOSS/SATIN
of 1 laag WIJZONOL ECO PRIMER S(N) + 1 laag WIJZONOL ECO TOPCOAT A GLOSS/SATIN
 Procescondities volgens bijlage G-1 of H van het KOMO productcertificaat 33200/23
 Minimale natte laagdikte laag 1 is 150µm
 Minimale natte laagdikte laag 2 is 150 µm

of **2 lagen WIJZONOL ECO TRANSPARANT ZIJDEGLANS**
 Procescondities volgens bijlage F van het KOMO productcertificaat 33200/23
 Minimale natte laagdikte laag 1 is 175µm
 Minimale natte laagdikte laag 2 is 175 µm

		Maandag		Dinsdag		Woensdag		Donderdag		Vrijdag	
		laag 1	laag 2	laag 1	laag 2	laag 1	laag 2	laag 1	laag 2	laag 1	laag 2
Plaats je laagdiktemeter in de verf en maak hiernaast een afdruk, volgens de instructies van SKH 98-04.	150										
	170										
	190										
	210										
	230										
	250										
	270										
	290										

Notities